



Designed for hotel applications

- > Compact unit (230mm high & 652mm deep), can easily be mounted in narrow ceiling voids
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- > Flexible installation, as the air suction direction can be altered from rear to bottom suction


FXDQ-M9



Indoor unit			FXDQ	20M9	25M9
Cooling capacity	Nom.		kW	2.2	2.8
Heating capacity	Nom.		kW	2.5	3.2
Power input - 50Hz	Cooling Nom. kW		kW	0.050	
	Heating Nom. kW		kW	0.050	
Dimensions	Unit	Height	mm	230	
		Width	mm	502	
		Depth	mm	652	
Required ceiling void > mm			mm	250	
Weight	Unit kg 17		7		
Casing	Colour			Unpainted	
	Material			Galvanised steel	
Fan-Air flow rate	Cooling	High/Low	m³/min	6.7/5.2	7.4/5.8
- 50Hz	Heating	High/Low	m³/min	6.7/5.2	7.4/5.8
Air filter	Туре			Resin net with mold resistance	
Sound power level	Cooling	Nom.	dBA	50	
Sound pressure level	Cooling High/Low dBA		dBA	37/32	
	Heating High/Low dBA		dBA	37/32	
Refrigerant	Type/ GWP			R-410A / 2.087,5	
Piping connections	Liquid OD mm		mm	6.35	
	Gas	OD	mm	12.7	
	Drain			I.D. 21.6, O.D. 27.2	
Power supply	Phase/Frequency/Voltage Hz/V		Hz/V	1~/50/230	
Current - 50Hz	Maximum fuse amps (MFA) A		A	16	
Control systems	Infrared remote control			BRC4C62	
	Simplified wired remote control for hotel applications			BRC2E52C (heat recovery type) / BRC3E52C (heat pump type)	
	Wired remote control			BRC1D52 / BRC1E52A/B	

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)





CPEN15-242

02/15



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.